

Versatile, Virtually Indestructible and Ready for the Extreme

Not just a camera enclosure but an engineered outdoor housing system that is designed to expand all indoor camera models into complete rugged outdoor system solutions.

Virtually Indestructible: We produce the world's toughest enclosures, will not corrode, rust, leak and has proven to withstand a whole world of abuse.

No matter the climate we take outdoor temperature protection very seriously: Extreme Hot climates, Cold climates, Marine and everywhere in between.



- Universal input voltages options: 24 VAC/VDC, 110 - 220 VAC.
- 12 VDC and 24 V camera and component power
- Easier, faster installation process - less time
- Works with most camera brands and models

innovative

ST-RF-MVP: Dotworkz S-Type Ring of Fire De-Icing Camera Enclosure with MVP



Description:

Unlike traditional small 5W singular heat-patch enclosures that often fog or ice over, the specialized circuitry of the Ring of Fire de-icing/defroosting system removes the snow and ice that would normally obstruct a camera's view.

Combined with the D-Series housing seals—which keeps out all moisture, dust and corrosive atmosphere—the Ring of Fire is the ideal solution for cold climate deployments.

Features:

- Enables IP and analog cameras to operate in freezing locations, with temperatures down to -60° F (-51° C)
- Includes Heavy Duty cast aluminum alloy STRONG ARM Wall Mount
- Thermostatically controlled De-Icing and Heating unit keeps internal electronics at ideal operating temperature
- Case is designed to be “vandal-tough,” and protect valuable electronics from damage and theft
- Multi-Volt Platform allows for effortless and professional installation
- Heavy-duty, non-metallic, non-corrosive, flame-resistant, Polycarbonate Thermal Plastic alloy case
- Housing exceeds IP66 rating: airtight and sealed against outside air, dust, insects, water, corrosion and other harsh conditions
- Extends the life and operating performance of all stored electronics
- Internal mounting space for IP hardware: routers, cell networks, NVR, hard drives, UPS, WiMax, mesh hardware, etc.

1 depends on camera being integrated

Specs:

Operating Temperature (Absolute):

-60° to 140°F (-51°C to 60°C)

Operating Temperature (Recommended):

-40° to 120°F (-40°C to 49°C)

Power Consumption:

3 amps @ 115 VAC typical at full load

MVP Input Power Source Options:

24VAC, 110 VAC, or 220 VAC

MVP Output Options for Camera Power:

12 VDC, 24 VDC

Internal Power Available for Camera:

12VDC & 24V of 26 watts total

Shipping: 24" x 10" x 10" - 11 lbs (5 Kg)



remote video solutions

www.dotworkz.com 866.575.4689